

SV-QSFP-100G-ER4

100GBase aggregating 4 x duplex LWDM wavelengths SM (LC) with DDM, distance up to 30km, supporting 100GE, Infiniband QDR and DDR



Features

- Hot pluggable QSFP28 MSA form factor
- Compliant to Ethernet 100GBASE-ER4 Lite
- Supports 103.1Gb/s aggregate bit rate
- Up to 30km reach for G.652 SMF without FEC
- Up to 40km reach for G.652 SMF with FEC
- Single +3.3V power supply
- Operating case temperature: 0~70°C
- Transmitter: cooled 4x25Gb/s LAN WDM EML TOSA (1295.56, 1300.05, 1304.58, 1309.14nm)
- Receiver: 4x25Gb/s APD ROSA
- 4x25G electrical interface (OIF CEI-28G-VSR)
- Maximum power consumption 4.5W
- Duplex LC receptacle

Applications

- 100GBASE-ER4 Ethernet Links
- Infiniband QDR and DDR interconnects
- Client-side 100G Telecom connections

Part number	Description
SV-QSFP-100G-ER4	Starview QSFP28 100Gbps module 100GBase aggregating 4 x duplex LWDM (1295.6 nm, 1300.1 nm, 1304.6 nm, and 1309.1nm) wavelengths SM (LC) with Digital Diagnostic Monitoring (DDM), distance up to 30km, supporting 100GE, Infiniband QDR and DDR

Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit
Storage Temperature	T _s	-40	85		°C
Operating Case Temperature	T _{OP}	0	70		°C
Power Supply Voltage	V _{CC}	-0.5	3.6		V
Relative Humidity (non-condensation)	RH	0	85		%
Damage Threshold, each Lane	TH _d	-3.0			dBm

Recommended Operating Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Operating Case Temperature	T _{OP}	0		70	°C	
Power Supply Voltage	V _{CC}	3.135	3.3	3.465	V	
Data Rate, each Lane			25.78125		Gb/s	
Data Rate Accuracy		-100		100	ppm	
Control Input Voltage High		2		V _{CC}	V	
Control Input Voltage Low		0		0.8	V	
Link Distance with G.652 (without FEC)	D1			30	km	1
Link Distance with G.652 (with FEC)	D2			40	km	1

Note(1): Depending on actual fiber loss/km (link distance specified is for fiber insertion loss of 0.4dB/km)

Optical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Lane Wavelength	L0	1294.53	1295.56	1296.59	nm	
	L1	1299.02	1300.05	1301.09	nm	
	L2	1303.54	1304.58	1305.63	nm	
	L3	1308.09	1309.14	1310.19	nm	
Transmitter						
SMSR	SMSR	30			dB	
Total Average Launch Power	P _T			10.5	dBm	
Average Launch Power, each Lane	P _{AVG}	-2.9		4.5	dBm	
OMA, each Lane	P _{OMA}	0.1		4.5	dBm	1
Difference in Launch Power between any Two Lanes (OMA)	P _{tx,diff}			3.6	dB	
Launch Power in OMA minus Transmitter and Dispersion Penalty (TDP), each Lane		-0.65			dBm	
TDP, each Lane	TDP			2.5	dB	
Extinction Ratio	ER	7			dB	
RIN _{20OMA}	RIN			-130	dB/Hz	
Optical Return Loss Tolerance	TOL			20	dB	

Transmitter Reflectance	R _t	-12	dB	
Average Launch Power OFF Transmitter, each Lane	P _{off}	-30	dBm	
Eye Mask{X1, X2, X3, Y1, Y2, Y3}		{0.25, 0.4, 0.45, 0.25, 0.28, 0.4}		
Receiver				
Damage Threshold, each Lane	TH _d	3.0	dBm	3
Average Receive Power, each Lane		-16.9	-4.9	dBm For 30km link distance
Average Receive Power, each Lane		-20.9	-4.9	dBm For 40km link distance
Receive Power (OMA), each Lane			-1.9	dBm
Receiver Sensitivity (OMA), each Lane	SEN1		-14.65	dBm for BER = 1x10 ⁻¹²
Stressed Receiver Sensitivity (OMA), each Lane			-12.65	dBm for BER = 1x10 ⁻¹²
Receiver Sensitivity (OMA), each Lane	SEN2		-18.65	dBm for BER = 1x10 ⁻¹²
Stressed Receiver Sensitivity (OMA), each Lane			-16.65	dBm for BER = 1x10 ⁻¹²
Receiver Reflectance	R _r		-26	dB
Difference in Receive Power between any Two Lanes (OMA)	Prx,diff		3.6	dB
LOS Assert	LOSA		-26	dBm
LOS Deassert	LOSD		-24	dBm
LOS Hysteresis	LOSH	0.5		dB
Receiver Electrical 3 dB upper Cutoff Frequency, each Lane	F _c		31	GHz
Conditions of Stress Reliever Sensitivity Test Note(4)				
Vertical Eye Closure Penalty, each Lane		1.5		dB
Stressed Eye J2 Jitter, each Lane		0.3		UI
Stressed Eye J9 Jitter, each Lane		0.47		UI

Note(1): The minimum average launch power spec is based on ER not exceeding 9.5dB and transmitter OMA higher than 0.1dBm.

Note(2): Even if the TDP < 0.75 dB, the OMA min must exceed the minimum value specified here.

Note(3): The receiver shall be able to tolerate, without damage, continuous exposure to a modulated optical input signal having this power level on one lane. The receiver does not have to operate correctly at this input power.

Note(4): Vertical eye closure penalty, stressed eye J2 jitter, and stressed eye J9 jitter are test conditions for measuring stressed receiver sensitivity. They are not characteristics of the receiver.

Digital Diagnostics Functions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Temperature monitor absolute error	DMI_Temp	-3		+3	degC	Over operating temperature range
Supply voltage monitor absolute error	DMI_VCC	-0.1		0.1	V	Over full operating range
Channel RX power monitor absolute error	DMI_RX_Ch	-2		2	dB	1
Channel Bias current monitor	DMI_Ibias_Ch	-10%		10%	mA	
Channel TX power monitor absolute error	DMI_TX_Ch	-2		2	dB	1

Note(1): Due to measurement accuracy of different single mode fibers, there could be an additional +/-1 dB fluctuation, or a +/- 3 dB total accuracy

Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Power Consumption				4.5	W	
Supply Current	I _{cc}			1.36	A	
Transmitter (each lane)						
Overload Differential Voltage pk-pk	TP1a	900			mV	
Common Mode Voltage (V _{cm})	TP1	-350		2850	mV	1
Differential Termination Resistance Mismatch	TP1			10	%	At 1MHz
Differential Return Loss (SDD11)	TP1			See CEI-28G-VSR Equation 13-19	dB	
Common Mode to Differential conversion and Differential to Common Mode conversion (SDC11, SCD11)	TP1			See CEI-28G-VSR Equation 13-20	dB	
Stressed Input Test	TP1a		See CEI-28G-VSR Section 13.3.11.2.1			
Receiver(each lane)						
Differential Voltage, pk-pk	TP4			900	mV	
Common Mode Voltage (V _{cm})	TP4	-350		2850	mV	1
Common Mode Noise, RMS	TP4			17.5	mV	
Differential Termination Resistance Mismatch	TP4			10	%	At 1MHz
Differential Return Loss (SDD22)	TP4			See CEI-28G-VSR Equation 13-19	dB	
Common Mode to Differential conversion and Differential to Common Mode conversion (SDC22, SCD22)	TP4			See CEI-28G-VSR Equation 13-21	dB	

Common Mode Return Loss (SCC22)	TP4		-2	dB	2
Transition Time, 20 to 80%	TP4	9.5		ps	
Vertical Eye Closure (VEC)	TP4		5.5	dB	
Eye Width at 10 ⁻¹⁵ probability (EW15)	TP4	0.57		UI	
Eye Height at 10 ⁻¹⁵ probability (EH15)	TP4	228		mV	

Note(1): Vcm is generated by the host. Specification includes effects of ground offset voltage.

Note(2): From 250MHz to 30GHz.